

## Display indicators on appliances with Convotherm 4 easyDial controls

### General

- These instructions are intended solely for a qualified installation engineer and an authorized customer service engineer.
- Inform the customer of important points relating to operation and safety.

### Intended use

These instructions provide an overview of all the possible indicators that can be shown on the display featured by appliances with easyDial controls.

### Necessary additional instructions

These instructions are a supplement to the user and installation manuals and the servicing documentation for your appliance and must only be used in conjunction with these documents. Please refer to the manuals for technical data, intended use, design and operation and safety information.

### Basic settings / setup

<i>Adj</i>	Settings
<i>Snd</i>	Volume
<i>d</i>	Day
<i>nn</i>	Month
<i>h</i>	Hours
<i>y</i>	Year
<i>nn</i>	Minutes
<i>C F</i>	Temperature display (°C/F)

### Cookbook functions

<i>P 1</i>	Program number P1 to P99 for cooking profiles
<i>S- 1</i>	Cooking profile containing one cooking step
<i>S- 3</i>	Cooking step 3 of a multistep cooking profile; up to 9 cooking steps are possible

## ConvoClean functions

<b>CLA</b>	Cleaning assistant cleaning profile, semi-automatic oven cleaning
<b>CLD</b>	Rinse-with-water cleaning profile
<b>CLC</b>	Cooking chamber descaling
<b>CLr</b>	Automatic safety rinsing after cleaning is cancelled
<b>BLF</b>	Boiler rinsing in progress
<b>ConvoClean cleaning profiles</b>	
<b>CL 1</b>	Cleaning level 1 for light soiling
<b>CL 2</b>	Cleaning level 2 for moderate soiling
<b>CL 3</b>	Cleaning level 3 for heavy soiling
<b>CL 4</b>	Cleaning level 4 for very heavy soiling
<b>CL 1d</b>	Cleaning level 1 for light soiling including steam disinfection and drying
<b>CL 2d</b>	Cleaning level 2 for moderate soiling including steam disinfection and drying
<b>CL 3d</b>	Cleaning level 3 for heavy soiling including steam disinfection and drying
<b>CL 4d</b>	Cleaning level 4 for very heavy soiling including steam disinfection and drying

### Update functions, import/export functions

<i>UPd</i>	Update
<i>b0</i>	UI-board, easyDial
<i>SI b</i>	SI board
<i>oUt</i>	Export
<i>I n</i>	Import
<i>HACC</i>	HACCP
<i>CLn</i>	Cleaning
<i>Pro</i>	Cookbook
<i>dEL</i>	Delete the cooking profile
<i>150 C</i>	Flashing dot on temperature display: gas burner on
<i>68 C</i>	Flashing dot on CTC display: cooking with sous-vide sensor
<i>E73_1</i>	Info after prolonged power outage in startup mode
<i>HACC oUt</i>	Export HACCP data
<i>Pro I n</i>	Import a cookbook
<i>Pro oUt</i>	Export a cookbook
<i>CLn1 I n</i>	Import a cleaning profile for cleaning using single-measure dispensing
<i>CLn2 I n</i>	Import a cleaning profile for cleaning using canisters
<i>UPd b0</i>	Perform a software update